



## TELESCOPIC MULTIFRAMER HANDLER 30.6 SERIES



### CHECK OUT THESE STANDARD FEATURES:

- Full power – direct drive PTO – variable travel speed
- Shift on the go 2 speed transmission – up to 40 kph
- Swing out engine – maximum accessibility
- Excellent visibility – spacious cab – 995mm wide – 360 degree vision
- Multipurpose – multi function single joystick – ease of operation

MODEL	30.6 Classic <sup>2</sup>	30.6 Top <sup>2</sup>
Maximum load capacity	3000 kg	3000 kg
Maximum lift height	6 metres	6 metres
Maximum forward reach	3.15 metres	3.15 metres
Load capacity at maximum height	3000 kg	3000 kg
Load capacity at maximum forward reach	1500 kg	1500 kg
4-cylinder engine (Euro 2)	Turbo aftercooler	Turbo aftercooler
Power rating at 2400 rpm (97/68/CE)	85 kW (115 HP)	85 kW (115 HP)
Transmission	Hydrostatic	Hydrostatic
Maximum speed	40 km/h	40 km/h
Total unladen mass (with forks)	6550 kg	6550 kg
Hydraulic pump	Gear type	Gear type
Rear Pto (standard)	540/1000 rpm	540/1000 rpm
Front Pto (optional)	1000 rpm	1000 rpm
Rear three-point linkage	Standard	Standard
Frame levelling device	Standard	Standard
Rear three point linkage load capacity	4300 kg	4300 kg
Control system	Conventional	Electronic MERlin
Towing capacity (European homologation)	Up to 20000 kg	Up to 20 000 kg
Tyres	17.5LR24	17.5LR24