



## LIGHTWEIGHT COMPACT HANDLING SYSTEMS



### CHECK OUT THESE STANDARD FEATURES:

- Up to 140 hp machines for the toughest jobs
- Multifunction Single Joystick for easy finger tip controls
- Boom suspension system available to smooth out the bumps
- Exclusive Portal axle design enables shorter chassis – longer wheel base
- Auto selecting Oscillating axles – changes with your work load

MODEL	P 34.7 PLUS	P 34.7 TOP	P 34.10 PLUS	P 34.10 TOP
Maximum load	3400 kg	3400 kg	3400 kg	3400 kg
Maximum lift height	7 metres	7 metres	9.7 metres	9.7 metres
Maximum forward reach	3.6 metres	3.6 metres	6.3 metres	6.3 metres
Capacity at maximum height	3400 kg	3400 kg	1200 kg	1200 kg
Capacity at maximum forward reach	1350 kg	1350 kg	600 kg	600 kg
Low emission (Euro 2) 4 cylinder engine	Turbo	Turbo	Turbo	Turbo
Power at 2400 rpm (97/68/CE)	74.9 kW (102 HP)	74.9 kW (102 HP)	74.9 kW (102 HP)	74.9 kW (102 HP)
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Maximum travel speed	40 kph	40 kph	40 kph	40 kph
Total unladen mass (with forks)	6600 kg	6600 kg	7250 kg	7250 kg
Boom sideshift	-	-	-	-
Frame Levelling	-	-	-	-
Hydraulic pump	Gear	Load-Sensing	Gear	Load-Sensing
Tyres	405/70-24	405/70-24	405/70-24	405/70-24

MODEL	P 36.7 PLUS	P 36.7 TOP	P 37.10 PLUS	P 37.10 TOP
Maximum load	3600 kg	3600 kg	3700 kg	3700 kg
Maximum lift height	7 metres	7 metres	9.7 metres	9.7 metres
Maximum forward reach	3.6 metres	3.6 metres	6.3 metres	6.3 metres
Capacity at maximum height	3600 kg	3600 kg	1200 kg	1200 kg
Capacity at maximum forward reach	1350 kg	1350 kg	600 kg	600 kg
Low emission (Euro 2) 4 cylinder engine	Turbo	Turbo	Turbo	Turbo
Power at 2400 rpm (97/68/CE)	74.9 kW (102 HP)	74.9 kW (102 HP)	103 kW (140 HP)	103 kW (140 HP)
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Maximum travel speed	40 kph	40 kph	40 kph	40 kph
Total unladen mass (with forks)	6760 kg	6760 kg	7250 kg	7250 kg
Boom sideshift	Standard	Standard	-	-
Frame Levelling	Standard	Standard	-	-
Hydraulic pump	Gear	Load-Sensing	Load-Sensing	LS Flow-Sharing
Tyres	405/70-24	405/70-24	405/70-24	405/70-24